

NexLog

Express Recording Solutions

EXP SERIES



NexLog EXP-M

The NexLog EXP-M recorder is the ideal portable recording solution for rugged applications. NexLog EXP-M captures and stores critical voice communications in harsh, remote, and off-grid environments.

With easy-to-use interfaces for audio replay, audio export, and system configuration, the *NexLog EXP-M* recorder is based on Eventide's highly reliable *NexLog DX-Series* recording software.

Use Cases

- Mobile Incident Command Vehicles
- Portable Incident Management Centers
- Fireground Command
- Police and Fire Vehicles
- Trains and Railway Networks
- Cargo Ships
- Remote Shelters
- Portable Carrying Cases

The Eventide logo is displayed in large, white, bold letters with a registered trademark symbol. It is overlaid on a photograph of a fire truck at night, with its emergency lights glowing. The truck is positioned in the lower half of the page, and the background is dark with some light trails from the lights.

Eventide®



Audio Recording Capabilities:

The NexLog EXP-M recorder is designed to record from 2-wire analog sources, 4-wire analog sources, and/or VoIP audio sources.

Automatic Archiving:

Each NexLog EXP-M recorder includes a license to archive recordings to one external device, such as a USB Hard Drive, USB Flash Drive, NAS, or a NexLog DX-Series recorder at HQ.

Remote Startup and Orderly Shutdowns:

Configurable ignition power control for vehicular use, with power-off delay of up to 24 hours.



Technical Specifications:

- 2U, short depth; Rack, Shelf or VESA mountable
- Dimensions: 3.11" (H) x 10.24" (W) x 8.46" (D)
- One PCIe slot for analog recording card
- Dual Solid-State Drives (RAID-1 mirrored)
- Over 80,000 hours of voice recording storage
- Dual 10/100/1000 Ethernet LAN ports
- Operating Temperature: -40°F to 167°F (-40°C to 75°C)
- EN50155 Compliant: Temp., Humidity, Vibration, Impact
- Power Input: +6 to +36 Volts DC (+14 VDC Typical)
- Surge Protected DC Input (+80V clamp)

Eventide®